



# **Material Safety Data Sheet**

NFPA	HMIS	Personal Protective Equipment
00	Health Hazard 2 Fire Hazard 2	
,	Reactivity	See Section 15.

Section 1. Chem	ical Product and Company Identification		Page Number: 1	
Common Name/ Trade Name	Kerosene	Catalog Number(s).	K1025	
		CAS#	8008-20-6 or 64742-81-0	
Manufacturer	SPECTRUM LABORATORY PRODUCTS INC.	RTECS	OA5500000	
	14422 S. SAN PEDRO STREET GARDENA, CA 90248	TSCA	TSCA 8(b) inventory: Kerosene	
Commercial Name(s)	Astral Oil; Coal Oil, Fuel Oil No. 5, Deobase, Astral Oil, Jet A Fu Jet Fuel JP-1; JP-5 Navy Fuel; Kerosine, petroleum; Range Oil; K1 Kerosene; Kerosene, hydrodesulfurized		Not available.	
Synonym	Kerosine	IN CASE OF	- IN CASE OF EMERGENCY CHEMTREC (24hr) 800-424-9300 CALL (310) 516-8000	
Chemical Name	Kerosene			
Chemical Family	Not available.	CALL (310) 5		
Chemical Formula	Not available.			
Supplier	SPECTRUM LABORATORY PRODUCTS INC. 14422 S. SAN PEDRO STREET GARDENA, CA 90248	_		

			Exposure Limits		
Name	CAS#	TWA (mg/m³)	STEL (mg/m³)	CEIL (mg/m³)	% by Weight
1) Kerosene	8008-20-6 or 64742-81-0				100

#### Section 3. Hazards Identification

Potential Acute Health Effects Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator). Severe over-exposure can result in death.

### Continued on Next Page

Kerosene		Page Number: 2
Potential Chronic Health Effects	Slightly hazardous in case of skin contact (sensitizer).  CARCINOGENIC EFFECTS: Not available.  MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast.  TERATOGENIC EFFECTS: Not available.  DEVELOPMENTAL TOXICITY: Not available.  The substance is toxic to the nervous system.  The substance may be toxic to blood, kidneys, liver, central nervous system (CNS).  Repeated or prolonged exposure to the substance can produce target organs damage. R highly toxic material may produce general deterioration of health by an accumulation in organs.	

Section 4. First A	id Measures
Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Serious Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Serious Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.
Ingestion	If swallowed, do NOT induce vomiting. If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Serious Ingestion	Not available.

Section 5. Fire and E	xplosion Data
Flammability of the Product	Flammable.
Auto-Ignition Temperature	210°C (410°F)
Flash Points	CLOSED CUP: 38°C (100.4°F). (Tagliabue.)
Flammable Limits	LOWER: 0.7% UPPER: 5% - 7%
Products of Combustion	Not available.
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames and sparks.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.
Fire Fighting Media and Instructions	Flammable liquid, insoluble in water.  SMALL FIRE: Use DRY chemical powder.  LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Not available.
Special Remarks on Explosion Hazards	Not available.

Kerosene	Page Number: 3
----------	----------------

Section 6. Accidental Release Measures		
Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.	
Large Spill	Toxic flammable liquid, insoluble or very slightly soluble in water. Poisonous liquid.  Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.	

Section 7. Handling and Storage		
Precautions	Keep locked up Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.	
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).	

Section 8. Exposure	Controls/Personal Protection
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Exposure Limits	Not available.

Section 9. Physical a	nd Chemical Properties		
Physical state and appearance	Liquid. (Oily liquid.)	Odor	Not available.
Molecular Weight	Not available.	Taste	Not available.
pH (1% soln/water)	Not applicable.	Color	Yellow. Clear (Light.)
Boiling Point	149°C (300.2°F) - 325 C		
Melting Point	Not available.		
Critical Temperature	Not available.		
Specific Gravity	0.775840(Water = 1)		
Vapor Pressure	0.1 kPa (@ 20°C)		
Vapor Density	4.5 (Air = 1)		
Volatility	Not available.		
Odor Threshold	Not available.		
Water/Oil Dist. Coeff.	Not available.		
Ionicity (in Water)	Not available.		
Dispersion Properties	Not available.		
Solubility	Insoluble in cold water, hot water. Miscible with other petroleum solvents		

## Continued on Next Page

Kerosene Page Number: 4

Stability	The product is stable.
Instability Temperature	Not available.
Conditions of Instability	Heat, ignition sources (sparks, flames), incompatible materials
Incompatibility with various substances	Reactive with oxidizing agents.
Corrosivity	Not considered to be corrosive for metals and glass.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.
Polymerization	Will not occur.

Polymerization	Will not occur.				
Section 11. Toxicological Information					
Routes of Entry	Absorbed through skin. Eye contact.				
<b>Toxicity to Animals</b>	Acute oral toxicity (LD50): 2835 mg/kg [Rabbit].				
Chronic Effects on Humans	MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. Causes damage to the following organs: the nervous system. May cause damage to the following organs: blood, kidneys, liver, central nervous system (CNS).				
Other Toxic Effects on Humans	Hazardous in case of skin contact (irritant), of ingestion, of inhalation (lung irritant). Slightly hazardous in case of skin contact (permeator).				
Special Remarks on Toxicity to Animals	Not available.				
Special Remarks on Chronic Effects on Humans	May affect genetic material (mutagenic)				
Special Remarks on other Toxic Effects on Humans	Acute Potential Health Effects: Skin: Causes moderate to severe skin irritation. It can cause defatting dermatitis. Eyes: May cause eye irritation. Inhalation: May cause respiratory tract and mucous membrane irritation and a burning sensation in the chest. Because of its relatively low volatility, overexposure by inhalation is uncommon, but it can occur in poorly ventilated areas or by inhalation of mists or aerosols. Symptoms of inhalation overexposure include central nevous system (CNS) depression (transient euphora, headache, irritability, excitement, ringing in the ears, weakness, incoordination, confusion, disorientation, drowsiness, tremor, somnolence, hallucinations, seizures, coma, death). May affect the heart (cardiac arrythmias), liver, kidneys, and respiration( asphyxia, apnea, acute pulmonary edema, dyspnea, fibrosis, or cyanosis) Ingestion: Causes gastrointestinal tract irritation with burning sensation in mouth, esophagus, and stomach, abdominal pain, nausea, vomitting, hypermotility, diarrhea, headache, malaise. May affect respiration/trachea/bronchi through accidental pulmonary aspiration which can cause hypoxia, chemical pneumonitis, and noncardiogenic pulmonary edema, pulmonary hemmorrhage, coughing, breathing difficulty, acute or chronic pulmonary edema, emphysema, respiratory stimulation. It may also affect the heart (dysrrhythmias, myocardial depression, tachycardia), liver, endocrine system (pancreas - hypoglycemia), behavior/central nervous system (symptoms similar to that of inhalation). Chronic Potential Health Effects: Inhalation: Repeated or prolonged inhalation may cause respiratory tract irritation and affect behavior/central nervous system with symptoms similar to that of acute inhalation. It may also affect the blood (changes in white blood cell count, changes in serum compositon, pigmented or nucleated red blood cells, leukopenia, normocytic anemia), cardiovascular system, respiratory system (trachea, bronchi), and may cause kidney damage. Ingestion: Repeated or prolonged skin co				

Page Number: 5

Section 12. Ecological Information			
Ecotoxicity	Not available.		
BOD5 and COD	Not available.		
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.		
Toxicity of the Products of Biodegradation	Not available.		
Special Remarks on the Products of Biodegradation	Not available.		

#### Section 13. Disposal Considerations

Waste Disposal Waste must be disposed of in accordance with federal, state and local environmental

control regulations.

#### Section 14. Transport Information

DOT Classification CLASS 3: Flammable liquid.

Identification : Kerosene UNNA: 1223 PG: III

**Special Provisions for** 

Transport

Not available.

DOT (Pictograms)



#### Section 15. Other Regulatory Information and Pictograms

Federal and State

Regulations

Connecticut hazardous material survey.: Kerosene Rhode Island RTK hazardous substances: Kerosene

Pennsylvania RTK: Kerosene Massachusetts RTK: Kerosene Massachusetts spill list: Kerosene

New Jersey: Kerosene

TSCA 8(b) inventory: Kerosene

California Proposition 65 Warnings			
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.		
Other Classifications	WHMIS (Canada)	CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). CLASS D-2B: Material causing other toxic effects (TOXIC).	
	DSCL (EEC)	R10- Flammable. R26/28- Very toxic by inhalation and if swallowed. R33- Danger of cumulative effects. R36/38- Irritating to eyes and skin. R65- Harmful: may cause lung damage if swallowed.	S23- Do not breathe gas/fumes/vapour/spray S24- Avoid contact with skin. S28- After contact with skin, wash immediately with plenty of water S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S62- If swallowed, do not induce vomiting: seek medical advice immediately and show this

#### Continued on Next Page

# Page Number: 6 Kerosene container or label. Health Hazard HMIS (U.S.A.) 2 **National Fire Protection** Flammability Association (U.S.A.) Fire Hazard 2 Health Reactivity Reactivity 0. Specific hazard Personal Protection h WHMIS (Canada) (Pictograms) **DSCL** (Europe) (Pictograms) TDG (Canada) (Pictograms) ADR (Europe) (Pictograms) **Protective Equipment** Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

Kerosene Page N	umber: 7
-----------------	----------

Section 16. Other Information		
MSDS Code	K3050	
References	Not available.	
Other Special Considerations	Not available.	
Validated by Sonia Owen on 3/28/2003.		Verified by Sonia Owen. Printed 9/25/2003.
2 1 T 1 (2 4 2 ) T 1 C 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		

#### CALL (310) 516-8000

**Notice to Reader** 

All chemicals may pose unknown hazards and should be used with caution. This Material Safety Data Sheet (MSDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this MSDS. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this MSDS is based on technical data judged to be reliable, Spectrum Quality Products, Inc. assumes no responsibility for the completeness or accuracy of the information contained herein.